

## Smart USB Charging Port Controller

### General Description

The NT6003 is a smart USB interface IC specifically designed for dedicated charging port applications. The NT6003 automatically identifies the handheld devices attached to the USB port. Then it emulates the genuine chargers accordingly so that the attached device can draw maximum current from the charging port.

The NT6003 supports Apple iPad, Apple iPhone, Samsung Galaxy Note, BC1.2 or YD/T 1591 compliant devices, and majority of modern portable devices.

The NT6003 is available in tiny TSOT23-5L package.

*Note: Apple, iPad, iPhone, Samsung and Galaxy Note are trademarks belonging to their respective owners.*

### Applications

- CLA Car Chargers
- Computer Peripherals
- Wall Adaptors
- USB Power Plugs
- Portable Power Banks

### Features


- 4.5V ~ 6.0V Single Supply Operation
- Smart USB Charger Identification Circuit
  - Support Apple iPad 2.4A Applications
  - Support Samsung Galaxy Note 2.0A Applications
  - Support BC1.2 & YD/T 1591 Battery Charging Specifications
- 8kV High ESD
- -40°C ~ +125°C Operating Ambient Temperature
- TSOT23-5L Package
- RoHS Compliant and Halogen-Free

### Ordering Information

Order Number	Package	Top Marking
NT6003AMT5	TSOT23-5L	N02

Note: EOSMEM products are compatible with the current IPC/JEDEC J-STD-020 requirement. They are halogen-free, RoHS compliant and 100% matte tin (Sn) plating that are suitable for use in SnPb or Pb-free soldering processes.


### Pin Configuration & Typical Application Circuit



## Functional Pin Description

Pin No.	Pin Name	Pin Function
1	SEL	<b>Operation Mode Selection.</b> This pin is internally pulled high by a 4.3uA current source.
2	GND	<b>Ground for the IC.</b> All voltage levels are measured with respect to this pin.
3	VCC	<b>Supply Voltage</b> to the IC.
4	DP	USB positive data-channel to external USB devices.
5	DM	USB negative data-channel to external USB devices.

## Functional Block Diagram



## Functional Description

The NT6003 is a smart USB interface IC specifically designed for universal power adaptors. It automatically detects the portable device attached to the USB port. Then it emulates the respective proprietary charger so that the portable device could be charged with its maximum rated current. The NT6003 supports Apple iPad, Apple iPhone, Samsung Galaxy Note, BC1.2 or YD/T 1591 compliant devices, and majority of modern portable devices.

### Automatic Detection of Data Lines

When powered up, the NT6003 starts with Apple mode and biases the data lines DP/DM at certain levels according to the SEL pin status as shown in Table 1. Then it detects status of DP/DM to identify the type of the attached device. If the DP/DM voltages remain within their respective levels, the NT6003 asserts that an *Apple* device is attached and keeps biasing the DP/DM pins at preset levels.

If the DP/DM voltages drift from their respective levels, the NT6003 asserts that a *non-Apple* device is attached and shorts the DP and DM pins by an internal switch.

### Mode Selection

Three operation modes are available selected by the SEL pin as shown in Table 1. The SEL pin is internally pulled high by a 4.3uA current source. Set the SEL pin according to current rating of the dedicated charging port.

**SEL = Middle.** If the dedicated charging port can provide current as high as 2.4A, connect a 470kΩ resistor from SEL pin to GND. The attached *iPad 4* can draw up to 2.4A charging current.

**SEL = High.** If the dedicated charging port can provide current as high as 2.1A, let the SEL pin floating. The attached *iPad* can draw up to 2.1A charging current.

**SEL = Low.** If the dedicated charging port can only provide current as high as 1.5A, short the SEL pin to GND. The attached *iDevice* can draw up to 1.0A charging current. If a BC1.2 compliant device is attached, it is allowed to draw up to 1.5A charging current.

Note that the NT6003 only controls behavior of data lines DP/DM of USB charging port. It does not involve any power related operation. The companion power converter must be capable of delivering 2.4A/2.1A/1.5A output current with rated output voltage according to the SEL status.

Table 1. Operation Mode Selection

Dedicated Charger Capability	SEL	iDevice			BC1.2 Compliant Device		
		DP	DM	Maximum Allowable Current	DP	DM	Maximum Allowable Current
> 2.4A	470kΩ to GND	2.8V	2.8V	2.4A	Short Circuit		1.5A
> 2.1A	Open	2.8V	2.1V	2.1A	Short Circuit		1.5A
> 1.5A	Short to GND	2.1V	2.8V	1.0A	Short Circuit		1.5A

## Absolute Maximum Rating

(Note1)

Supply Input Voltage, $V_{CC}$	-----	-0.3V to +7V
Other Pins	-----	+0.3V to ( $V_{CC} + 0.3V$ )
Storage Temperature Range	-----	-55°C to +150°C
Operation Temperature Range	-----	-40°C to +125°C
Lead Temperature Range (Soldering 10sec)	-----	260°C
ESD Rating (Note2)		
MM (Machine Mode)	-----	500V
HBM (Human Body Mode)	-----	8kV

## Thermal Information

Package Thermal Resistance (Note3)

TSOT23-5L $q_{JA}$	-----	250°C/W
TSOT23-5L $q_{JC}$	-----	100°C/W
Power Dissipation, $P_D$ @ $T_A = 25^\circ\text{C}$		
TSOT23-5L	-----	0.4W

## Recommended Operating Conditions

Operating Junction Temperature Range (Note4)	-----	-40°C to +125°C
Operating Ambient Temperature Range	-----	-40°C to +125°C

**Note 1.** Stresses listed as the above "Absolute Maximum Ratings" may cause permanent damage to the device. These are for stress ratings. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may remain possibility to affect device reliability.

**Note 2.** Devices are ESD sensitive. Handling precaution recommended.

**Note 3.**  $q_{JA}$  is measured in the natural convection at  $T_A = 25^\circ\text{C}$  on a high effective thermal conductivity test board of JEDEC 51-7 thermal measurement standard.







**Note 4.** The device is not guaranteed to function outside its operating conditions.

**Electrical Characteristics**


 ( $V_{CC} = 5V$ ,  $T_A = +25^{\circ}C$  unless otherwise specified.)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
<b>Supply Input</b>						
Supply Voltage Range	$V_{CC}$		4.5	--	6.0	V
Quiescent Current	$I_{CC}$	SEL pin open	--	0.45	0.52	mA
<b>SEL</b>						
SEL Pin Pull High Current	$I_{SEL}$	$V_{SEL} = 2.4V$	3.6	4.3	5.0	$\mu A$
Logic High Threshold Level	$V_{SEL-H}$	$V_{SEL}$ Rising	--	$V_{CC}-1.5$	$V_{CC}-1.0$	V
Logic Low Threshold Level	$V_{SEL-L}$	$V_{SEL}$ Falling	0.6	1.0	--	V
Logic Middel Range	$V_{SEL-M}$		1.5	--	$V_{CC} - 2$	V
<b>DP/DM</b>						
DP Floating Voltage	$V_{DP}$	$V_{SEL} = \text{High, Middle}$	2.7	2.8	2.9	V
		$V_{SEL} = \text{Low}$	2.0	2.1	2.2	
DM Floating Voltage	$V_{DM}$	$V_{SEL} = \text{Low, Middle}$	2.7	2.8	2.9	V
		$V_{SEL} = \text{High}$	2.0	2.1	2.2	
DP Pin Output Impedance	$Z_{DP}$		32	40	48	kW
DM Pin Output Impedance	$Z_{DM}$		32	40	48	kW
DP Rising Threshold for Exiting Apple Mode, Delta from DP Floating Voltage	$V_{DP-R}$	$V_{SEL} = \text{High, Middle}$	50	--	200	mV
		$V_{SEL} = \text{Low}$	100	--	400	
DM Falling Threshold for Exiting Apple Mode	$V_{DM-F}$	$V_{SEL} = \text{Low, Middle}$	2.0	2.1	2.2	V
		$V_{SEL} = \text{High}$	1.4	1.5	1.6	
DP and DM Short Circuit Switch		Non-Apple device attached	55	70	95	W
DP/DM Terminal Voltage		$V_{SEL} = \text{High, Middle}$	1.1	1.2	1.3	V
<b>Timing</b>						
Delay Time for Exiting Apple Mode		$V_{DP} > V_{DP-R}$	1.3	1.7	2.1	ms
Delay Time for Exiting Apple Mode		$V_{DM} < V_{DM-F}$	80	100	120	ms
Recycle Time for Entering Apple Mode			1.6	2.0	2.4	s
Pulse Width for Retrying to Apple Mode			1.6	2.0	2.4	ms




## Typical Operation Characteristics



### TSOT23-5L



Recommended Solder Pad Layout



#### Note

##### 1. Package Outline Unit Description:

BSC: Basic. Represents theoretical exact dimension or dimension target

MIN: Minimum dimension specified.

MAX: Maximum dimension specified.

REF: Reference. Represents dimension for reference use only. This value is not a device specification.

TYP: Typical. Provided as a general value. This value is not a device specification.

##### 2. Dimensions in Millimeters.

##### 3. Drawing not to scale.

##### 4. These dimensions do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.15mm.